



## WOOD REVIVER POWER-GEL

Highly effective cleaning and refreshing of greyed wood!



6609  
Clear



### PRODUCT DESCRIPTION

Gelatinous cleaner for refreshing and cleaning greyed wood in outdoor areas. Wood Reviver Power-Gel is a non-drip product, and so it is easy to apply – especially on vertical surfaces. The gel penetrates the wood deeply and removes grey patina. Through subsequent re-oiling, the fresh warm wood colour is restored.

### RECOMMENDED USE

Osmo Wood Reviver Power-Gel is highly recommended for timber decking, cladding, garden furniture and similar surfaces.

### INGREDIENTS

Osmo Wood Reviver Power-Gel contains biodegradable oxalic acid (< 5 %). This product is free of solvents, formaldehyde, chlorine compounds and amines. Detailed declaration of ingredients available upon request.

### TECHNICAL DATA

Specific gravity: 0.99-1.05 g/cm<sup>3</sup>  
Viscosity: >70s DIN EN ISO 2431/3 mm, thixotropic  
Odour: faint/mild, after drying odourless  
Flash point: not applicable

### STORAGE

Up to 2 years and longer if container is kept dry, closed tightly and stored at temperatures between 5 and 35°C. Do not expose to frost during transport!

### SURFACE PREPARATION

Remove debris from greyed wood; afterwards dampen with water. Wood Reviver Power-Gel is ready to use. Do not thin. Perform a trial application before treating wood with Wood Reviver Power-Gel.

### METHODS OF APPLICATION

Generously apply the gel along the wood grain. After approx. 20 minutes reaction time, clean surface with Osmo Decking Cleaning Brush and rinse with a lot of water. After drying for approx. 48 hours, protect the newly refreshed wood with a wood finish (e.g. Osmo Natural Oil Woodstain, Decking-Oils, Country Colour). For machine processing on decking, we recommend using Osmo Decking and Flooring Cleaner.

### CLEANING OF TOOLS

Immediately after use, with soap and water.

### DRYING TIME

Approx. 24-48 hours (normal climatic conditions, 23 °C/50 % rel. humidity). Lower temperatures and/or higher air humidity can increase the drying time. Ventilate well while drying.

### COVERAGE

1 litre covers approx. 10 m<sup>2</sup> with one application. Coverage depends significantly on the condition of the wood. All information refers to smooth and planed/sanded surfaces. Other surfaces may lead to differences in coverage.

### NOTE

Protect metal (e.g. hinges) and plants against direct contact (e.g. cover ornamental and farm plants with a tarpaulin.)

### CAUTION

Keep out of reach of children. Do not get in eyes, on skin, or on clothing. If medical advice is needed, have product container or label at hand. Observe the general safety regulations when handling chemicals. Safety data sheet available on request.



## DISPOSAL

Dispose of leftover product and completely emptied packaging according to local official guidelines (waste code number 20 01 29). Only completely emptied cans can be recycled.

## COLOUR TONES

6609 Clear

## CAN SIZES

0.5 L; 2.50 L; 5.00 L; 10.00 L

The above mentioned information is provided to the best of our knowledge however without any liability.

Version 02/18