

DIAMOND EGGSHELL

Dulux Trade Diamond Eggshell is a tough and cleanable emulsion with a smooth, even mid sheen finish. It contains **Anti-Fade Technology*** to protect colour pigment from damage for truly long-lasting colour** and beautiful results. It's perfect for busy environments that require frequent cleaning as it contains unique **Stain Repellent Technology**, preventing stains from setting in to the surface and making cleaning up easier. It also protects against common scuffs and achieves Class 1 ISO 11998 and Type C BS 7719 scrub ratings, meaning walls withstand daily wear and tear and the finished job looks freshly painted for longer.

*Anti-Fade technology in Magnolia and tinting bases only

** All coloured paints will show signs of fading over time as a result of UV and pollutant exposure, with different colours fading at different rates. Diamond with Anti-Fade technology will slow down the effects of this exposure, prolonging the life of your colour

KEY BENEFITS

- Ultimate Durability
- Contains scrub, scuff and stain resistant technology
- Repeatedly cleanable, perfect for high traffic areas

PRODUCT INFORMATION

Typical Use

Suitable for interior use on plaster and masonry.
Also suitable for use in kitchens and bathrooms.
Do not use externally.

Pack Size

1L, 2.5L and 5L.

Colour Range

See appropriate **Dulux Trade** colour literature or visit duluxtrade.co.uk.

Film Properties

Chemical Resistance: Not recommended.

Heat Resistance: Not recommended for use on heated surfaces, such as radiators.

Water Resistance: Resistant to the levels of atmospheric humidity present in normal interior environments and will withstand repeated

washing. Suitable for use in kitchens and bathrooms. Not suitable for use on immersed surfaces or where there is heavy and prolonged condensation.

Film Thickness

Film thickness will be dependent on the coverage achieved.

Wet: 63 microns.

Dry: 23 microns.

Composition (nominal)

Pigment: Lightfast Pigments.

Binder: Acrylic Copolymer Emulsion.

Solvent: Water.

Volume Solids

White – 37% (nominal). Other colours will vary.

SURFACE PREPARATION

Walls and Ceilings:

To get the best results with **Dulux Trade** Diamond Eggshell on walls and ceilings, make sure surfaces to be painted are sound, clean, dry (new surfaces particularly must be fully dry) and

DIAMOND EGGSHELL

free from all defective or poorly adhering material such as loose paint, dirt, grease and waxes. New or bare surfaces should be mist coated with an appropriate **Dulux Trade** product e.g. Fast Matt, Drywall Primer.

SYSTEMS INFORMATION

STIR THOROUGHLY BEFORE USE. Seal new or bare surfaces with a thinned first coat of **Dulux Trade** Diamond Eggshell (up to 1 part clean water to 10 parts paint). The normal finishing process is 2 full coats of **Dulux Trade** Diamond Eggshell, however for significant colour change additional coats may be required.

For best colour consistency, purchase sufficient tinted paint for each job including touch-in at one time from the same source.

APPLICATION METHOD

Brush, roller, conventional spray or airless spray.

Do not use when the temperature is below 10°C.

To minimise picture framing or patchy finishes, we strongly recommend stirring the paint thoroughly prior to use. If thinned, the paint used for cutting-in and for rolling should be to the same ratio. Cut in one wall at a time, then rolling immediately afterwards, not allowing the cutting-in to dry prior to rolling. Cut in no more than 5 to 8cm away from any internal angles, including sockets/switches, skirting, architraves, etc. Roll into the cutting-in, ensuring you roll as close to the edge as possible.

Practical Coverage

A guide to the practical coverage which can be achieved under normal conditions is up to 16m² per litre.

Thinning

Sealing new or bare surfaces: Add up to 1 part clean water to 10 parts paint.

Normal use (not to be exceeded): Thinning is not usually required.

Conventional spray application: Add up to 1 part clean water to 5 parts paint.

Airless spray application: Thinning is not usually required.

Spray Recommendations

HVLP: Use a #5/2.2mm fluid set and dilute as required

Airless Spray: For broadwall surfaces use a standard tip e.g. 517. For more complex surfaces consider using a fine finish/low pressure tip for best results

Drying Times

Single coat at standard thickness:

Touch Dry: Dependent on temperature and humidity.

Recoat: 4-6 hours, although will vary according to temperature and humidity (e.g. will take significantly longer in cold, damp conditions).

Cleaning Up

After use, remove as much product as possible from equipment before cleaning with water.

When this paint container is empty please ask your stockist about recycling. If you have leftover paint, please dispose of it responsibly and consider donating it to **Community RePaint**.



Issued 010/19

408

DIAMOND EGGSHELL

Find out more at

www.duluxtradepaintexpert.co.uk/products/sustainability.

Cleaning Recommendations for Painted

Surface: Common stains can be removed by cleaning promptly with a soft cloth and clean soapy water. Allow to dry. Vigorous scrubbing and the use of abrasive cleaners or scourers may impair the eggshell finish. Only apply enough pressure to remove marks. Some oil-based stains and marks from some pens/felt tips/permanent markers may not be completely removed. Full durability develops 7 days after initial application. For information about removing specific stains, please phone the **AkzoNobel** Technical Advice Centre on 0333 222 70 70.

Transportation & Storage

Do not use or store in extremes of temperature and protect from frost. To prevent spillage, please store and transport upright.

VOC

EU limit value for this product (cat.: A/a): 30g/l (2010).

Ready Mixed: This product contains max. 17g/l VOC. VOC content: Low (0.30-7.99%).

Tinted Colour: This product contains max. 22g/l VOC. VOC content: Low (0.30-7.99%).

FURTHER SUPPORT

If you need further support, please contact the **AkzoNobel** Technical Advice Centre on 0333 222 70 70.

Always read full Health, Safety & Environmental Information on can before use.

Safety datasheet (SDS 408) is available free on request by telephoning the **AkzoNobel** Technical Advice Centre or by visiting duluxtrade.co.uk.

AkzoNobel, the AkzoNobel logo, the Flourish logo, Dulux Trade, Diamond Technology, Polycell, Polyfilla and Community RePaint are trademarks of the AkzoNobel group. © AkzoNobel 2019.