

FILL-FLEX

FIBACRYL

FLEXIBLE FILLER FOR GAPS & CRACKS

- ◆ ADHERES TO PLASTER, MASONRY, PRIMED WOOD & PAINTWORK
- ◆ HIGHLY FLEXIBLE: WILL NOT CRACK
- ◆ MOVES WITH THE SUBSTRATE
- ◆ NO NEED TO SPOT PRIME



PURPOSE

Ready to use all purpose flexible filler, suitable for new and renovated surfaces on interiors and exteriors. Can fill up to 1cm.

SUBSTRATES

Fill-Flex can be applied to any substrate either unpainted or painted:

- Gypsum plaster, plaster tiles, plasterboards, mortars
- Old painted surfaces, concrete, cellular concrete
- Cement, breeze blocks, bricks, stones and primed wood.

OVERCOATING

Fill-Flex can be overcoated with any type of filler, paint or wall coating.

Physical and technical FEATURES

- Fill-Flex: filler in ready mixed form for interior and exterior use made of mineral extracts and selected resin.
- Characterization (NFT 36-005): Family IV Class 4b.
- Codification (EN 16-566): G₃S₂V₀W₀A₀C₀R₀.
- Mixing rate: ready to use.
- Application thickness: up to 1cm.
- Capacity: 1kg fills 0.70L.
- Setting time: second coat as soon as the filler is hard and dry to the touch.
- Overcoating: can be painted in 24 to 48 hours average time (after complete drying).
- Color: white.
- Adhesion: filler/substrate (EN 16-566): > 0.8 Mpa.

USE AND STORAGE CONDITIONS

- Application tools: filling knife, trowel or blade.
- Remove excess filler with a wet sponge immediately after application.
- Tool cleaning: after use, product residue can be rubbed off tools when dry (water cleaning is not necessary).
- Preservation: guaranteed for 12 months from purchase when used as intended, kept in its original sealed packaging and stored away from sunlight and frost.

If found to be faulty within the guarantee period, we will arrange a replacement on proof of purchase.

PACKAGING

Cartridge: 310ml.
Tub: 1kg.

RECOMMENDATIONS and care for use

The times mentioned are indicative and depend on the substrate, coat thickness, and the ambient conditions.

Do not apply at a temperature below 5°C or above 35°C nor at a relative humidity over 80%.

SUBSTRATES PREPARATION

Substrates to be prepared as per the current trade practices. Substrates must be hard, cohesive, clean, sound and dry.

NORMATIVE DOCUMENTS to be referred to

- BS EN 16566:2014 (Paints and varnishes. Fillers for internal and/or external works).

HEALTH AND SAFETY

It is recommended to wear gloves and glasses while applying Fill-Flex.

Always wear a dust mask when sanding.

Dispose of unused product and packaging responsibly at your local waste collection centre.

Preservatives: Contains 1,2-benzisothiazolin-3-one; C(M)IT / MIT (3:1); MBIT. May produce an allergic reaction.

Safety data sheet available at www.toupret.co.uk

The data sheet information, especially the guidelines relevant to the application and final use of the product are provided in good faith and result from TOUPRET's experience and knowledge of the products. The product should be used as per the trade practices rules book and in reference to our recommendations. The information provided is relevant to applications processed at a temperature of 20°C, a relative humidity of 50% and on average absorbency substrates. The times mentioned are only indicative and depend on the substrate, the coat thickness, and the ambient conditions.



* Information on the emission level of volatile substances into indoor air, presenting a risk of toxicity by inhalation, on a scale from A+ (very low emissions) to C (high emissions).