

READY MIXED FILLER

Description

Ready mixed filler

Intended use

- Filling small holes and cracks



Product advantages

- + Excellent adhesion to substrates
- + Easy to apply
- + Dries hard
- + Easy to sand
- + Will not flash or grin
- + No need to spot prime



ENVIRONMENTAL DATA

INDOOR AIR EMISSIONS

Information on the level of emissions of volatile substances into indoor air presenting a risk of toxicity by inhalation, on a class scale from A+ (very low emissions) to C (high emissions)



COMPOSITION

83% OF RAW MATERIALS
OF NATURAL ORIGIN

Calcium carbonate, polysaccharide, water, sugar

V.O.C CONTENT

VOC Directive 2004/42/EC: Cat A/a EU limit value: 30 g/L

This product contains a maximum 1 g/L PAE

PACKAGING

Contain at least 30% recycled plastic
Not recyclable

MANUFACTURING

This product is manufactured in our factory whose environmental management system is certified by Afnor



Beissier is committed to the sustainable development of its activities and has integrated CSR into its strategy our company has achieved an exemplary level on the "Engagé RSE label" assessment benchmark



READY MIXED FILLER

USE

DILUTION

Ready mixed

APPLICATION

▪ Conditions

Do not apply at temperatures of below + 5°C or above + 35°C, or at a relative humidity of above 80% H.R.

▪ Equipment

Filling knife, blade

▪ Equipment cleaning

With water before completely dry. Do not throw away into drains, dispose of this material and its container to an approved disposal contractor or taken to municipal collection point. Do not dispose into the environment.

AVERAGE CONSUMPTION

0,5 kg/m²

(Depending on application thickness)

SUBSTRATES

Concrete, cellular concrete, cement, concrete block, brick, plaster, plasterboard, old painted substrates.

Substrates must be hard, cohesive, clean, sound and dry according to the local standards.

OVERCOAT

Primer, filler, conventional paint, light-weight wall coverings

WORKING TIME AT 20°C

Unlimited

WAITING TIME BEFORE OVERCOATING

Once completely dry

TECHNICAL DATA

COMPONENTS

Polymer base aqueous phase coat mix, mineral fillers, additives.

DENSITY

1,7 ± 0,1

pH

8 ± 1

COLOUR

White

CLASSIFICATION

NF T 36-005 - Family IV, class 4b

NORM

NF EN 16566

HEALTH AND SAFETY



Use in a well-ventilated place. Avoid direct contact with skin and eyes. In case of prolonged contact, it is recommended to wear suitable gloves. Application by projection, wearing glasses and a mask is recommended. Safety data sheet available on www.beissier.eu or www.quickfds.com

PACK SIZES

1 kg bucket

STORAGE

12 months from date of manufacture, in unopened original packaging, protected from frost, heat (max. +30°C), sun and moisture. Close well after use. Store in original packaging.

This data sheet supersedes and replaces any prior sheet relating to the same product. Date of issue : **July 2025**

The purpose of this data sheet is to inform our customers about our product's properties. The information presented in the sheet is based on the current state of our knowledge. However, this information is no substitute for a description pertaining specifically to the type and condition of the substrate concerned. Since technical progress is continuously being made, it is our customer's responsibility, prior to use, to check with us that updated edition of this sheet has not been issued.



France - Quartier de la Gare, 77760 La Chapelle la Reine
Becket House - 1 Lambeth Palace Road - London - SE1 7EU

020 7092 6696 • www.beissier.eu

FOLLOW US ON



FIND MORE ABOUT US THROUGH OUR NETWORK

